

HUBER+SUHNER® DATA SHEET

Sencity Antenna: 1319.26.0027



Rev.: T

SPA-1900/85/8/0/DS

Description

DECT
Polarization: dual linear, $\pm 45^\circ$ slant
indoor

Product Configuration

Technical Data

Electrical Data

	Band 1
Frequency (MHz)	1880 - 1930
VSWR	1.5
Gain	8 dBi
3dB beamwidth (h) ($^\circ$)	85
3dB beamwidth (v) ($^\circ$)	75
Front to back ratio	12 dB
Vertical electrical tilt ($^\circ$)	0
Isolation between port	30 dB

General Data

Nominal impedance	50 Ω
Polarisation	$\pm 45^\circ$ slant
Connector	TNC, jack (female), bottom
Composite power max.	75 W at ambient temperature 25 $^\circ$ C

Mechanical Data

Dimensions (mm)	101 x 95 x 32 (Height x Width x Depth)
Weight	0.11 kg
Windload	frontal: 15 N at km/h
Included mounting material	Wall mounting material
Mounting socket material:	ASA and aluminium
Mounting socket colour:	RAL 7042 (dark grey)

Environmental Data

Environmental conditions	outdoor
Operation temperature ($^\circ$ C)	-40 to 80
Storage temperature ($^\circ$ C)	-40 to 80
Transport temperature ($^\circ$ C)	-40 to 80
RoHS 2002/95/EC	compliant

Material Data

Radome colour	RAL 7035 (light-grey)
Radome material	ASA (Acrylic Styrene Acrylonitrile)
Back plate/base plate colour	RAL 7042 (dark-grey)
Back plate/base plate material	Aluminium

Related Products

9091.99.0029 Pol Bracket
9091.99.0080 Sidetilt Bracket



HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Industrial
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions

HUBER+SUHNER® DATA SHEET

Sencity Antenna: 1319.26.0027

Rev.: T



Related Documents

Mounting instruction	DOC-0000197953
Painting instruction	DOC-0000256180
Security instruction	DOC-0000278984
Outline drawing1	DOU-00018841

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Industrial
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions