

HUBER+SUHNER® DATA SHEET

Coaxial Cable: SUCOFEED_7/8_EC

Description

Corrugated coaxial cable



Technical Data

Construction

	Material	Detail	Diameter	
Centre conductor	Copper	Tube	typ. 9	mm
Dielectric	SPE (Foamed Polyethylene)		typ. 22	mm
Outer conductor	Copper	Tube (c), 100 %	typ. 24.7	mm
Jacket	PE-LD	Black	27.4	mm +/- 0.25
Print	HUBER+SUHNER_SUCOFEED_7/8_EC_#batch-number#_#metric-length#			

Electrical Data

Impedance	50	Ω +/- 1
Operating frequency	≤ 5	GHz
Capacitance	typ. 76.5	pF/m
Inductance	typ. 0.2	μ H/m
Velocity of signal propagation	typ. 87	%
Signal delay	typ. 3.8	ns/m
Insulation resistance	$\geq 1 \times 10^7$	M Ω m
Screening effectiveness	≥ 120	dB
Operating voltage	≤ 3	kV _{rms} (at sea level)
Test voltage	6	kV _{rms} (50 Hz/1 min)
Outer conductor resistance DC	≤ 1.3	Ω /km
Inner conductor resistance DC	≤ 1.48	Ω /km

Mechanical Data

Weight	≤ 45.3	kg/100 m
Bending radius	static	≥ 120 mm
	repeated (for ≤ 15 bendings)	≥ 250 mm
Tensile strength	≤ 1400	N
Bending force moment	≤ 37	Nm
Flat Plate Crush Resistance	1.4	kg/mm

Environmental Data

Temperature range	-40 °C... + 85 °C
Installation temperature	-25 °C... + 60 °C
Halogen test	IEC 60754-1
2002/95/EC (RoHS)	compliant

Additional Information

Remarks

(For details contact your nearest HUBER+SUHNER partner)

Suitable Connectors

Cable group M23

Suitable Tools

Cable tool 74_Z-0-23-16

Suitable Grounding Kit

Cable grounding kit 9076.99.N078 9076.99.P078

HUBER+SUHNER® DATA SHEET

Coaxial Cable: SUCOFEED_7/8_EC



Rev.: B

Matrix **typical Attenuation** [formula: $(a \cdot f^{0.5} + b \cdot f)$] and **maximum Power CW** [formula: $(P/f^{0.5})$]

Coefficients:

a=	0.036097419 typ.	b=	0.005025812 typ.	f _{max.} =	5	P ≤	2410
						at 1GHz	
	Frequency		Nom. attenuation		Nom. attenuation		Max. CW power
	(GHz)		(dB / 100 m)		(dB / 100 ft)		(watt)
			sea level 20° C ambient temperature		sea level 20° C ambient temperature		sea level 40° C ambient temperature
	0.100		1.19		0.36		7621
	0.150		1.47		0.45		6223
	0.174		1.59		0.48		5778
	0.200		1.71		0.52		5389
	0.400		2.48		0.76		3811
	0.450		2.65		0.81		3593
	0.500		2.80		0.85		3408
	0.512		2.84		0.87		3368
	0.800		3.63		1.11		2694
	0.894		3.86		1.18		2549
	0.960		4.02		1.23		2460
	1.000		4.11		1.25		2410
	1.500		5.17		1.58		1968
	1.700		5.56		1.69		1848
	1.800		5.75		1.75		1796
	1.880		5.89		1.80		1758
	2.000		6.11		1.86		1704
	2.200		6.46		1.97		1625

Matrix **typical Return Loss**

	Frequency		Frequency		Frequency		
	Range 1		Range 2		Range 3		
	(MHz)		(MHz)		(MHz)		
	380 to 470		806 to 960		1710 to 2200		
	typ. 28.5 dB		typ. 28.5 dB		typ. 26 dB		

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!
It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Protection
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 47 51
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions