

HUBER+SUHNER® DATA SHEET

Coaxial Cable Connector: 11_N-50-7-44/133_N



Description

Straight cable plug

Interface Standards

IEC 61169-16_MIL-STD-348A/304_CECC 22210



Technical Data

Electrical Data

| | |
|--------------------------|-------------|
| Impedance | 50 Ω |
| Interface frequency max. | 11 GHz |
| Frequency range | DC to 2 GHz |
| Return loss | ≥ 30 dB |

Mechanical Data

| | |
|----------------|-----------|
| Centre contact | crimped |
| Outer contact | crimped |
| Weight | 0.0291 kg |

Environmental Data

| | |
|-----------------------|------------------|
| Operating Temperature | -65 °C to 165 °C |
| 2002/95/EC (RoHS) | compliant |

Material Data

Piece Parts

| | Material | Surface Plating |
|----------------|-----------------------|-----------------------------------|
| Centre contact | Brass | Gold Plating (Nickel underplated) |
| Outer contact | Brass | SUCOPLATE (R) Plating |
| Body | Brass | SUCOPLATE (R) Plating |
| Insulator | PFA / PTFE | |
| Coupling nut | Brass | SUCOPLATE (R) Plating |
| Gasket | MVQ (Silicone Rubber) | |
| Crimp ferrule | Brass | SUCOPLATE (R) Plating |

Related Documents

| | |
|----------------------|----------------|
| Outline drawing | DOU-00006130 |
| Catalogue drawing | DOU-00006132 |
| Assembly instruction | DOC-0000179092 |

Ordering Information

| | |
|----------------------|---------------------|
| Single package | 11_N-50-7-44/133_NE |
| Bulk 100 pcs package | 11_N-50-7-44/133_NH |

Additional Information

| | |
|-----------------|-------------------------------------|
| Suitable cables | RG_214_U, GX_07272_D, GX_07272_D-04 |
|-----------------|-------------------------------------|

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions