

# HUBER+SUHNER® DATA SHEET

## Coaxial Cable Connector: 11\_N-75-4-6/133\_N

Rev.: B 

### Description

Straight cable plug

Interface Standards

IEC 60169-16\_MIL-STD-348A/304\_CECC 22210



### Technical Data

#### Electrical Data

Impedance 75  $\Omega$   
Interface frequency max. 1.5 GHz

#### Mechanical Data

Centre contact soldered  
Outer contact clamped  
Weight 0.0336 kg

#### Environmental Data

Operating Temperature -65 °C to 165 °C  
2002/95/EC (RoHS) compliant

#### Material Data

##### Piece Parts

Centre contact	Brass
Outer contact	Brass
Body	Brass
Insulator	PFA / PTFE
Coupling nut	Brass
Gasket	MVQ (Silicone Rubber)

##### Surface Plating

Gold Plating (Nickel underplated)
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating

#### Related Documents

Catalogue drawing	DOU-00006125
Assembly instruction	DOC-0000179335

#### Ordering Information

Single package	11_N-75-4-6/133_NE
----------------	--------------------

#### Additional Information

Suitable cable	G_04233_D
----------------	-----------

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



**HUBER+SUHNER AG**  
RF Technology  
9100 Herisau, Switzerland  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
www.hubersuhner.com

**HUBER+SUHNER – Excellence in Connectivity Solutions**