

# HUBER+SUHNER® DATA SHEET

## Coaxial Cable Connector: 11\_N-50-3-5/133\_N

Rev.: B



### Description

Straight cable plug

Interface Standards

IEC 61169-16\_MIL-STD-348A/304\_CECC 22210



### Technical Data

#### Electrical Data

Impedance 50  $\Omega$

Interface frequency max. 11 GHz

#### Mechanical Data

Centre contact soldered

Outer contact clamped

Weight 0.0365 kg

#### Environmental Data

Operating Temperature -65 °C to 165 °C

2002/95/EC (RoHS) compliant

#### Material Data

##### Piece Parts

Centre contact

Outer contact

Body

Insulator

Coupling nut

Gasket

##### Material

Brass

Brass

Brass

PFA / PTFE

Brass

MVQ (Silicone Rubber)

##### Surface Plating

Gold Plating (Nickel underplated)

SUCOPLATE (R) Plating

SUCOPLATE (R) Plating

SUCOPLATE (R) Plating

#### Related Documents

Outline drawing DOU-00008106

Catalogue drawing DOU-00006125

Assembly instruction DOC-0000177464

#### Ordering Information

Bulk 100 pcs package 11\_N-50-3-5/133\_NH

Single package 11\_N-50-3-5/133\_NE

#### Additional Information

Suitable cables RG\_223\_/U, ENVIROFLEX\_142, RG\_142\_B/U, RG 400 /U

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



**HUBER+SUHNER AG**

**RF Technology**

**9100 Herisau, Switzerland**

Phone +41 (0)71 353 41 11

Fax +41 (0)71 353 45 90

www.hubersuhner.com

**HUBER+SUHNER – Excellence in Connectivity Solutions**