



DATE TUE, 09-OCT-2007 09:49:53

PRINT OUT CLOSE WINDOW

## COAXIAL CABLE CONNECTORS ONLINE DATA BASE

[New selection](#)

### Item details

Jump to [\[Mechanical data\]](#) [\[Electrical data\]](#) [\[Environmental data\]](#) [\[Material\]](#) [\[Cable types\]](#)

### Item description

**11\_QLA-01-2-11/122\_NE**

#### Connector Description

Straight cable plug

#### Series / Pattern

• QLA-01 – Type / [Pattern 11](#)

#### Highlights



#### Item number

22544536

#### Catalogue drawing

[11\\_QLA-01-2-11](#)

#### Related documents

[Assembly Instruction](#)

#### 2002/95/EC (RoHS)

compliant

#### Interface Standards

NIM-CAMAC-Standard CD/N549

### Mechanical data

Jump to [\[Top\]](#)

#### Cable Entry Centre Contact

soldered

#### Cable Entry Outer Contact

clamped

#### Dielectric Size

2

### Electrical data

Jump to [\[Top\]](#)

#### Impedance

other

#### Interface Freq max

≤1.4 GHz

### Environmental and general data

Jump to [\[Top\]](#)

#### Operating Temp min

-55 °C

#### Operating Temp max

150 °C

#### Weight

0.0041 kg

#### Number of Matings

10000

#### Cable Retention Force

Value considers max. load without irreversible variations of specifications

125 N

### Material data

Jump to [\[Top\]](#)

#### 2002/95/EC (RoHS)

compliant

### Piece part

#### Base material

#### Plating

#### Center contact

Brass

Gold Plating (Nickel underplated)

#### Outer contact

Brass

Nickel Plating

#### Insulator

PFA / PTFE

#### Body

Brass

Nickel Plating

#### Crimp ferrule

Brass

Nickel Plating

### Suitable cable types

Jump to [\[Top\]](#)

#### Cable1

[RG\\_316\\_U](#)

Item number 22510079

#### Cable2

[ENVIROFLEX\\_316](#)

Item number 23009565

#### Cable3

[RG\\_188\\_A/U](#)

Item number 22510046

#### Cable5

RG 174 /U

### Related products

Jump to [\[Top\]](#)

#### • Adaptors

Show list