

HUBER+SUHNER® DATA SHEET

Coaxial Cable Connector: 11_QLA-01-2-9/122_N



Description

Straight cable plug

Interface Standards
NIM-CAMAC-Standard CD/N549



Technical Data

Electrical Data

Impedance other Ω
Interface frequency max. 1.4 GHz

Mechanical Data

Centre contact crimped
Outer contact crimped
Weight 0.0041 kg

Environmental Data

Operating Temperature -55 °C to 150 °C
2002/95/EC (RoHS) compliant

Material Data

Piece Parts

Centre contact	Brass
Outer contact	Brass
Body	Brass
Insulator	PFA / PTFE
Crimp ferrule	Copper

Surface Plating

Gold Plating (Nickel underplated)
Nickel Plating
Nickel Plating
SUCOPLATE (R) Plating

Related Documents

Outline drawing	DOU-00006914
Catalogue drawing	DOU-00006116
Assembly instruction	DOC-0000180105

Ordering Information

Bulk 100 pcs package 11_QLA-01-2-9/122_NH

Additional Information

Suitable cables K_02252_D, ENVIROFLEX_316_D, G_02232_D

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions