

# HUBER+SUHNER® DATA SHEET

## Coaxial Panel Connector: 22\_SHV-50-0-6/133\_N



### Description

Straight bulkhead receptacle jack

Interface standards

IEC 60498\_MIL-STD-348A/314



### Technical Data

#### Electrical Data

Impedance 50 Ω  
Interface frequency max. 0.3 GHz

#### Mechanical Data

Chassis torque 2 Nm  
Weight 0.0111 kg

#### Environmental Data

Operating Temperature -55 °C to 100 °C  
2002/95/EC (RoHS) compliant

#### Material Data

##### Piece Parts

Piece Parts	Material
Centre contact	Brass
Outer contact	Brass
Body	Brass
Insulator	PS
Fastening nut	Brass
Washer	Bronze

##### Surface Plating

Gold Plating (Nickel underplated)  
SUCOPLATE (R) Plating  
SUCOPLATE (R) Plating  
  
SUCOPLATE (R) Plating  
SUCOPLATE (R) Plating

### Related Documents

Outline drawing DOU-00011058  
Catalogue drawing DCA-00010449  
Mounting hole DOU-00008762

### Ordering Information

Single package 22\_SHV-50-0-6/133\_NE

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



**HUBER+SUHNER AG**  
**RF Technology**  
**9100 Herisau, Switzerland**  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
www.hubersuhner.com

**HUBER+SUHNER – Excellence in Connectivity Solutions**