

# HUBER+SUHNER® DATA SHEET

## Coaxial Panel Connector: 22\_SMA-50-0-3/111\_N

Rev.: A



### Description

Straight bulkhead receptacle jack

Interface standards

IEC 60169-15\_MIL-STD-348A/310\_CECC 22110



### Technical Data

#### Electrical Data

Impedance 50  $\Omega$   
Interface frequency max. 18 GHz

#### Mechanical Data

Weight 0.0022 kg

#### Environmental Data

Operating Temperature -65 °C to 165 °C  
2002/95/EC (RoHS) compliant

#### Material Data

##### Piece Parts

Centre contact  
Outer contact  
Body  
Insulator  
Fastening nut  
Washer

##### Material

Copper Beryllium Alloy  
Copper Beryllium Alloy  
Copper Beryllium Alloy  
PFA / PTFE  
Brass  
Bronze

##### Surface Plating

Gold Plating (Nickel underplated)  
Gold Plating (Nickel underplated)  
Gold Plating (Nickel underplated)  
  
Gold Plating (Nickel underplated)  
Gold Plating (Nickel underplated)

### Related Documents

Catalogue drawing DCA-00010437  
Mounting hole ML98

### Ordering Information

Single package 22\_SMA-50-0-3/111\_NE

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



**HUBER+SUHNER AG**  
RF Technology  
9100 Herisau, Switzerland  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
www.hubersuhner.com

**HUBER+SUHNER – Excellence in Connectivity Solutions**