

HUBER+SUHNER® DATA SHEET

Coaxial Cable Connector: 24_N-50-2-4/133_N



Description

Straight bulkhead cable feed through

Interface Standards

IEC 61169-16_MIL-STD-348A/304_CECC 22210



Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 11 GHz

Mechanical Data

Centre contact crimped
Outer contact crimped
Weight 0.0352 kg

Environmental Data

Operating Temperature -65 °C to 165 °C
2002/95/EC (RoHS) compliant

Material Data

Piece Parts

Centre contact	Copper Beryllium / Brass
Outer contact	Brass
Body	Brass
Insulator	PFA / PTFE
Gasket	NR (Natural Rubber)
Fastening nut	Brass
Washer	Bronze
Crimp ferrule	Copper

Surface Plating

Gold Plating (Nickel underplated)
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating

Related Documents

Outline drawing	DOU-00009130
Catalogue drawing	DCA-00009132
Assembly instruction	DOC-0000179123

Ordering Information

Bulk 100 pcs package	24_N-50-2-4/133_NH
Single package	24_N-50-2-4/133_NE

Additional Information

Suitable cables RG_316_U, ENVIROFLEX_316, RG_188_A/U, RG 174 /U

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions