

# HUBER+SUHNER® DATA SHEET

## Coaxial Cable Connector: 24\_QLA-01-1-11/112\_N

Rev.: A



### Description

Straight panel bulkhead cable jack, flange mount

Interface standards

NIM-CAMAC-Standard CD/N549



### Technical Data

#### Electrical Data

Impedance other  $\Omega$   
Interface frequency max. 1.4 GHz

#### Mechanical Data

Centre contact soldered  
Outer contact clamped  
Weight 0.0044 kg

#### Environmental Data

Operating Temperature -55 °C to 150 °C  
2002/95/EC (RoHS) compliant

#### Material Data

##### Piece Parts

Centre contact	Copper Beryllium Alloy
Outer contact	Bronze
Body	Brass
Insulator	PFA / PTFE
Fastening nut	Brass
Washer	Brass

##### Surface Plating

Gold Plating (Nickel underplated)
Gold Plating (Nickel underplated)
Nickel Plating
Nickel Plating
Nickel Plating
Nickel Plating

#### Related Documents

Catalogue drawing	DCA-00009270
Assembly instruction	DOC-0000180116
Mounting hole	ML99

#### Ordering Information

Single package	24_QLA-01-1-11/112_NE
Bulk 100 pcs package	24_QLA-01-1-11/112_NH

#### Additional Information

Suitable cables RG\_178\_B/U, ENVIROFLEX\_178, RG\_196\_A/U

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



**HUBER+SUHNER AG**  
RF Technology  
9100 Herisau, Switzerland  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
www.hubersuhner.com

**HUBER+SUHNER – Excellence in Connectivity Solutions**