

HUBER+SUHNER® DATA SHEET

Coaxial Cable Connector: 24_QMA-50-2-3/133_N



Description

Straight bulkhead cable feed through

Interface Standards
QMA QLF compliant



Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 6 GHz

Mechanical Data

Centre contact soldered
Outer contact crimped
Weight 0.0043 kg

Environmental Data

Operating Temperature -40 °C to 85 °C
2002/95/EC (RoHS) compliant

Material Data

Piece Parts

| | |
|----------------|------------------------|
| Centre contact | Copper Beryllium Alloy |
| Outer contact | Brass |
| Body | Brass |
| Insulator | PFA / PTFE |
| Gasket | MVQ (Silicone Rubber) |
| Fastening nut | Brass |
| Washer | Bronze |
| Crimp ferrule | Copper |

Surface Plating

| |
|-----------------------|
| SUCOPRO Plating |
| SUCOPLATE (R) Plating |
| SUCOPLATE (R) Plating |
| SUCOPLATE (R) Plating |
| SUCOPLATE (R) Plating |
| SUCOPLATE (R) Plating |
| SUCOPLATE (R) Plating |

Related Documents

| | |
|----------------------|----------------|
| Outline drawing | DOU-00009505 |
| Catalogue drawing | DCA-00008995 |
| Assembly instruction | DOC-0000179456 |
| Mounting hole | DOU-00008748 |

Ordering Information

| | |
|----------------------|----------------------|
| Single package | 24_QMA-50-2-3/133_NE |
| Bulk 100 pcs package | 24_QMA-50-2-3/133_NH |

Additional Information

Suitable cables RG_316_/U, ENVIROFLEX_316, RG_188_A/U, RG 174 /U

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions