

HUBER+SUHNER® DATA SHEET

Coaxial Cable Connector: 25_N-50-3-9/133_N

Rev.: D 

Description

Straight panel cable jack, flange mount

Interface Standards

IEC 61169-16_MIL-STD-348A/304_CECC 22210



Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 11 GHz

Mechanical Data

Centre contact soldered
Outer contact soldered
Weight 0.0413 kg

Environmental Data

Operating Temperature -65 °C to 165 °C
2002/95/EC (RoHS) compliant

Material Data

Piece Parts

Centre contact	Copper Beryllium Alloy
Outer contact	Brass
Body	Brass
Insulator	PFA / PTFE

Surface Plating

Gold Plating (Nickel underplated)
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating

Related Documents

Outline drawing	DOU-00009216
Catalogue drawing	DCA-00009218
Assembly instruction	DOC-0000350737
Mounting hole	DOU-00008795

Ordering Information

Single package	25_N-50-3-9/133_NE
Bulk 100 pcs package	25_N-50-3-9/133_NH

Additional Information

Suitable cables EZ_141_TP_M17, SUCOFORM_141, MULTIFLEX_141

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions