

HUBER+SUHNER® DATA SHEET

Within Series Adapter: 34_BNC-50-0-6/100_N

Rev.: E 

Description

Bulkhead adaptor jack/jack
BNC jack (female) / BNC jack (female)

Interface standards
IEC 60169-8_MIL-STD-348A/301_CECC 22120



Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	4 GHz
Frequency range	DC to 4 GHz
Return loss	≥ 15 dB

Mechanical Data

Number of matings	500
Weight	0.0232 kg

Environmental Data

Operating Temperature	-65 °C to 165 °C
2002/95/EC (RoHS)	not compliant

Material Data

Piece Parts (BNC)

Centre contact	Copper Beryllium Alloy
Outer contact	Copper Beryllium Alloy
Body	Copper Beryllium Alloy
Insulator	PFA / PTFE
Gasket	NR (Natural Rubber)

Piece Parts (BNC)

Centre contact	Copper Beryllium Alloy
Outer contact	Copper Beryllium Alloy
Body	Copper Beryllium Alloy
Insulator	PFA / PTFE
Gasket	NR (Natural Rubber)

Surface Plating

Gold Plating (Nickel underplated)
Silver Plating
Silver Plating

Surface Plating

Gold Plating (Nickel underplated)
Silver Plating
Silver Plating

Related Documents

Catalogue drawing	DCA-00013677
Mounting hole	DOU-00008751

Ordering Information

Single package	34_BNC-50-0-6/100_NE
----------------	----------------------

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!
It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions