

HUBER+SUHNER® DATA SHEET

Within Series Adaptor: 34_N-50-0-3/133_N



Description

Bulkhead adaptor jack/jack
N jack (female) / N jack (female)

Hermetic sealed connector

Interface standard

Series N - IEC 61169-16_MIL-STD-348A/304_CECC 22210



Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	18 GHz
VSWR	DC - 11 GHz $\leq 1.08 + 0.13 f$ (GHz)

Mechanical Data

Number of matings	500
Weight	0.0519 kg

Environmental Data

Operating Temperature	-65 °C to 165 °C
2002/95/EC (RoHS)	not compliant

Material Data

Piece Parts

Interface - N jack (female)

	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator		

Interface - N jack (female)

Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator		

Related Documents

Outline drawing	DOU-00013620
-----------------	--------------

Ordering Information

Single package	34_N-50-0-3/133_NE
----------------	--------------------

Remarks

Hermetic sealed

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions